

# Premier Compact HE INT

The **Kinetico Premier Compact** with e-max technology combines maximum performance and eco-efficiency in a compact design for the ultimate in soft water convenience.

## Functions:



This innovative, non-electric two tank technology combines optimum efficiency and maximum performance to give an unparalleled level of limescale prevention 24/7.



Precision engineered valve to operate quietly for minimum disturbance and noise level. It operates at particularly quiet levels while still delivering a consistently high performance.



Non-Electric



Compact Design



Metered Regeneration



Salt Viewing Window



Magnetic Lid



**PERFECT**  
WATER SYSTEMS LTD

## Specifications

part number: 16145

Dimensions	
Cabinet Dimensions (h x w x d)	219 x 468 x 498 mm
Transport Weight	17 kg
Performance	
	<b>HE INT</b>
Minimum Flow	0,19 l/min
Flow @ 1 bar Pressure Drop	22,7 l/min
Regeneration	
Salt Usage / Salt Capacity	0,34 kg / 8 kg
Regeneration Time	11 minutes
Volume	20,5 liter
System	
Media Volume	2 x 4,5 liter
Pipe Connections - in/out	¾" bsp male
Min/max Operating Temperature	2 - 23 °C
Min/max Operating Pressure	1,8 - 6 bar

Meter Disc		1	2	3	4	5	6	7	8
Max Hardness	gpg	4	9	13	17	21	25	28	30
	ppm	77	152	226	300	370	440	490	528
	°dH	4	9	13	17	21	25	28	30
	°TH	8	15	23	30	37	44	50	52
Litres between regenerations		1961	980	654	490	392	327	280	245